Accessories for the distribution network

Taps, 1-way

EAC 12	272327
EAC 16	272328
EAC 22	272329

- Impedance: 75 Ω
- Due to the wide frequency range of 0.15-2,150 MHz, suitable for house networks, community networks, CATV house distribution installations and satellite systems
- Conform to: EN 60728-11 and EN 50083-2
- For indoor mounting

EAC 12

Type			EAC 12	EAC 16	EAC 22
Order no.			272327	272328	272329
Frequency range		MHz	0.15-2,150 [1]	0.15-2,150 [1]	0.15-2,150
Tap loss		dB	10.5	13.5	20
Through loss	0.15-47 MHz 47-862 MHz 862-2,150 MHz	dB	1.5 1.1 1.8	1.5 0.7 1.4	0.8 0.8 1.0
Directional loss (output → tap)	47-2,150 MHz Minimal value	dB	≥ 28.5 [2] 20.5	≥ 31.5 [2] 23.5	- -
Screening factor	5-300 MHz 300-470 MHz 470-950 MHz 950-2,150 MHz	dB	≥ 85 ≥ 80 ≥ 75 ≥ 55		
Clamp connection		mm Ø	Inner conductor 0.4-1.6 Outer conductor 4.5-5.8 (7.9)		
Dimensions		mm	88.5 x 30 x 75		
Packing unit/weight		pc./kg	1 (100)/0.20		

[1] EAC 12/EAC 16. Data deviation in LMK range
[2] Relating to 40 MHz, -1.5 dB/octave